

INVOICE

Customer #:	34354419
Payment Terms:	Net 30
Invoice #:	2351714
Invoice Date	2026-08-05
Total Due	\$0.00

www.blueridgeenergy.com | 1-800-726-0405

THOMAS WAYNE & SHARON JONES

5044 SAPONY CREEK DRIVE
NASHVILLE, NC 27856

Make Check Payable to: Blue Ridge Energy, LLC

Amount Enclosed: \$

Remit To:
Blue Ridge Energy, LLC
PO Box 2008
Lenoir, NC 28645

003435441900023517140000000000000000000000

Customer Name		Delivery/Service Address	Cust #	Invoice #	Inv Date
THOMAS WAYNE & SHARON JONES		7974 THREE TOP RD - TODD, NC 28684	34354419	2351714	2026-08-05
Quantity	Item Number	Description	Unit Price	TOTAL	
1.00	6202545	Rinnai Tankless Water Heater	\$972.0100	\$972.01	
1.00	White Goods Disposa	White Goods Disposal Tax	\$3.0000	\$3.00	
1.00	Install Labor	Installation Labor	\$200.0000	\$200.00	
1.00		PreBuy Adjustment	-\$242.0700	-\$242.07	
1.00		Security Deposit Adjustment	-\$1,014.9800	-\$1,014.98	
		Ashe County Tax:	\$26.37		
		North Carolina State Tax:	\$55.67		

Tank/Equipment: Fuel Tank - Leased 320 LP Tank 1004563

For Fuel or Service At:

7974 THREE TOP RD - TODD, NC 28684

Sub Total	-\$82.04
Charges	\$0.00
Tax Total	\$82.04
0 TOTAL DUE	\$0.00

08/05/2026 - Technician: Eric Anders - Work Performed: - Replaced water heater, did not use vent pipe and no materials

Blue Ridge Energy, LLC
PO Box 2008
Lenoir, NC 28645

SERIAL #: WE. UA-049718



Model #: RE160i (REU-VE2125FFD-US)
ASSEMBLED IN GRIFFIN 23-3199

CSA/ANSI Z21.10.3 - CSA 4.3-2019



SANITATION

This water heater requires a special venting system. Refer to the installation instructions for parts list and method of installation. This equipment complies with the requirements of ASHRAE Standard 90.1.

Type of Gas:

Input Rating

Maximum:

Minimum:

Maximum Inlet Gas Pressure:

Minimum Inlet Gas Pressure:

Min. Inlet Gas Pressure For

Manifold Pressure-High Fire:

Manifold Pressure-Low Fire:

Maximum Water Pressure:

Nox Emissions:

Propane Gas
160,000 BTU/H
10,400 BTU/H
13.0"W.C. / (3.24kPa)
8.0"W.C. / (1.99kPa)
Adjustments: 11.0"W.C. / (2.74kPa)
4.5"W.C. / (1.12kPa)
1.1"W.C. / (0.27kPa)
150psi
<77ppm

Suitable for combination water (potable) heating and space heating and not suitable for space heating applications only

Direct-Vent Automatic Instantaneous Water Heater
DIRECT VENT AUTOMATIC INSTANTANEOUS WATER HEATER
FOR INSTALLATION IN A MANUFACTURED HOME (MOBILE HOME)

Minimum clearances from combustibles and non-combustibles:
Back: 0
Sides: 2" (51mm)
For Closet Installation, 6" from front

Front: 0

Ground: 1/2" (30.5mm)

Top: 2" (51mm)

Rinnai
Nagoya, Japan