

www.parkergas.com

GREGORY WARREN

220 Naylor School Rd. Roseboro, NC 28382

INVOICE

Customer #:		3006414
Payment Terms:		Net 30
	Invoice #:	4906407
	Invoice Date	2025-02-11
	Total Due	\$2,679.53

Make Check Payable to: Parker Gas Co. Inc.

Amount Enclosed: \$

Remit To: Parker Gas Co. Inc. P.O. Box 2590 Clinton, NC 28329-2590

00030064140004906407000026795300002679531

Customer Name		Delivery/Service Address	Cust # Invoice		Inv Date
		220 Naylor School Rd Roseboro, NC 28382	3006414	4906407	2025-02-11
Quantity	Item Number	Description	Unit Pri	се	TOTAL
1.00	RINNAI PLUMB KIT	PLUMBING KIT-RINNAI WATER HEATER	\$71	.0000	\$71.0
1.00	RE180ILP	RINNAI WATER HEATER-RE199I NON CONDENSING INDOORS Serial Number: PH.UA-068086	\$991	.0000	\$991.0
1.00	223182	RINNAI DIRECT VENT KIT-21" FOR NON CONDENSING UNITS	\$101	.0600	\$101.0
9.00	3/4CTS RED PEX PIF	3/4CTS RED PEX PIPE(1ft)	\$1	.1200	\$10.0
7.00	3/4CTS PEX WHITE I	3/4CTS PEX WHITE PIPE(1ft)	\$1	.1200	\$7.8
16.00	3/4IN PEX COPPER	3/4IN PEX COPPER CRIMP RING	\$0	.5800	\$9.2
7.00	3/4IN PEX 90 LF BRA	3/4IN PEX 90 LF BRASS	\$6	.4800	\$45.3
3.00	3/4IN PEX COUPLIN	3/4IN PEX COUPLING LF BRASS	\$8.2600		\$24.7
2.00	3/4IN SHARKBITE C	3/4IN SHARKBITE COUPLING	\$11.5800		\$23.1
1.00	TRUCK SUPPLIES	TRUCK SUPPLIES	\$7	.9500	\$7.9
25.00	3/4IN PROFLEX	PROFLEX CSST-3/4" ARC-RESISTANT (BLACK) (25' INCLUDED IN INSTALLATION)	\$C	.0000	\$0.0
2.00	3/4IN PROFLEX FITT	PROFLEX MALE FITTING-3/4"	\$18	.0200	\$36.0
2.00	3/4IN PROFLEX TER	PROFLEX TERMINATION PLATE W/FITTING-3/4"	\$26.8700		\$53.7
1.00	3/4IN MAXITROL	APPLIANCE REGULATOR-3/4" MAXITROL LP	\$85	.0600	\$85.0
3.00	3/4IN GALV UNION	GALVANIZED UNION-3/4" SCH 40	\$13	.5700	\$40.7
3.00	3/4IN GALV STREET	GALVANIZED STREET ELL-3/4"	\$6	.0000	\$18.0
1.00	3/4IN GALV TEE	GALVANIZED TEE-3/4"	\$6	.6700	\$6.6
1.00	3/4IN GALV CAP	GALVANIZED CAP-3/4 SCH 40	\$7	.1200	\$7.1
4.00	3/4IN X CLOSE GAL\	GALVANIZED NIPPLE-3/4 X CL SCH 40	\$6	.3700	\$25.4
1.00	3/4IN X 2IN GALV NII	GALVANIZED NIPPLE-3/4" X 2"	\$2	.3600	\$2.3
1.00	3/4IN FPT CUTOFF V	CUTOFF VALVE-3/4 FPT X 3/4 FPT	\$25	.2800	\$25.2
2.00	1/2IN FPT CUTOFF	1/2" FEMALE PIPE THREAD CUTOFF VALVE	\$18	.0900	\$36.1
1.00	1/2IN COPPER	COPPER-1/2" OD REFRIGERATION	\$0	.0000	\$0.0
4.00	1/2IN FLARE NUT	FLARE NUT-1/2"	\$3	.6200	\$14.4
1.00	1/2IN FLARE TEE	1/2" FLARE TEE	\$5	.0200	\$5.0
5.00	1/2IN X CLOSE GAL\	GALVANIZED NIPPLE-1/2" X CL SCH 40	\$3	.6300	\$18.1
3.00	1/2IN FLARE X 1/2IN	ADAPTER-1/2" FL X 1/2" MALE PIPE THREAD	\$4.8100		\$14.4
1.00	1/2IN GALV UNION	GALVANIZED UNION-1/2" SCH 40	\$10	.1400	\$10.1
1.00	3/4IN X 1/2IN GALV F	GALVANIZED REDUCING COUPLING-3/4" X 1/2"	\$4	.7600	\$4.7
1.00	LV3403TR9	REGULATOR-REGO COMPACT FIRST STAGE POL X 1/2	\$0	.0000	\$0.0
1.00	LV4403B4	REGULATOR-REGO SECOND STAGE 1/2 X 1/2	\$64	.3800	\$64.3



www.parkergas.com

GREGORY WARREN

220 Naylor School Rd. Roseboro, NC 28382

INVOICE

Customer #:		3006414
Payment Terms:		Net 30
	Invoice #:	4906407
	Invoice Date	2025-02-11
	Total Due	\$2,679.53

Make Check Payable to: Parker Gas Co. Inc.

Amount Enclosed: \$

Remit To: Parker Gas Co. Inc. P.O. Box 2590 Clinton, NC 28329-2590

00030064140004906407000026795300002679531

Cu	ustomer Name	Delivery/Service Address	Cust #	Invoice	# Inv Date
		220 Naylor School Rd Roseboro, NC 28382	3006414	490640	7 2025-02-11
Quantity	Item Number	Description	Unit Pri	ce	TOTAL
1.00	LV4403Y4	REGULATOR-REGO SECOND STAGE 2 PSI 1/2 X 1/2	\$68	8.8000	\$68.80
2.00	PRESTO TAP	PRESTO TAP- 1/4"FL X 1/8" MP	\$4	.9300	\$9.86
1.00	POL X POL X 20IN P	PIGTAIL-POL X POL X 20"	\$C	0.0000	\$0.00
4.00	Labor-2	Labor-2	\$160	0.0000	\$640.00
5.00	3/4IN PROFLEX	PROFLEX CSST-3/4" ARC-RESISTANT (BLACK)	\$4	.6500	\$23.25
1.00	White Goods Tax	White Goods Tax	\$3	3.0000	\$3.00
		NC State Sales Tax: Sampson County NC Sales Tax:			\$118.82 \$56.29

Tank/Equipment: Fuel Tank - TANK: 120 PROPANE

For Fuel or Service At:		Sub Total	\$2,504.42
220 Naylor School Rd Roseboro, NC 28382		Charges	\$0.00
		Tax Total	\$175.11
ACCOUNT BALANCE	\$2,719.72	TOTAL DUE	\$2,679.53

02/11/2025 - Technician: Peter Hill - Work Performed: Appliance Install - 2/11/25- Customer wanted a tankless interior water heater installed. Tech removed the old tanked water heater and installed a tankless 180i water heater and vented it out for the customer. Tech installed water lines from the old existing water heater and connected them to the new water heater. Tech ran new gas lines from the stub out to the water heater and connected them on a 2PSI system. New regulators had to be installed because the existing regulator was a twin stage. Leak tested/P3- no leaks found. Lit appliances and showed customer how to use them. OK EB 2/27/25

> Parker Gas Co. Inc. P.O. Box 2590 Clinton, NC 28329-2590

www.parkergas.com

IF YOU SMELL GAS



1.NO FLAMES OR SPARKS! Immediately put out all smoking materials and other open flames. Do not operate lights, appliances, telephones, or cell phones. Flames or sparks from these sources can trigger an explosion or a fire.

2. LEAVE THE AREA IMMEDIATELY! Get



everyone out of the building or area where you suspect gas is leaking.

3. SHUT OFF THE GAS. Turn off the main gas supply valve on your propane tank if it 6 is safe to do so. To close the valve, turn it to the right (clockwise)

ment.



4. REPORT THE LEAK. From a neighbor's home or other nearby building away from the gas leak, call your propane retailer right away. If you can't reach your propane

retailer, call 911 or your local fire depart-



5. DO NOT RETURN TO THE BUILDING OR

AREA until your propane retailer determines that it is safe to do so.



6. GET YOUR SYSTEM CHECKED. Before you attempt to use any of your propane appliances, your propane retailer or a qualified service technician must check your entire system to ensure that it is leak-free.

CAN YOU SMELL IT?



Propane smells like rotten eggs, a skunk's spray, or a dead animal, Some people may have difficulty smelling propane due to their age (older people may have a less sensitive sense of smell); a medical condition: or the effects of medication, alcohol, tobacco, or drugs. Consider purchasing a propane gas detector as an additional measure of security.

ODOR FADE is an unintended reduction in the concentration of the odor of propane. making it more difficult to smell. Although rare, several situations can cause odor fade:

- The presence of air, water, or rust in a propane tank or cylinder
- The passage of leaking propane through the soil



Since there is a possibility of odor fade or problems with your sense of smell, you should respond immediately to even a faint odor of gas.

PROPANE GAS DETECTORS

Propane Gas Detectors sound an alarm if they sense propane in the air. They can provide an additional measure of security in homes with little-used areas or with occupants who have difficulty smelling propane.

GUIDELINES regarding propane gas detectors:



· Buy only units that are listed by Underwriters Laboratories (UL).

- · Follow the manufacturer's instructions regarding installation and maintenance.
- · Never ignore the smell of propane, even if no detector is sounding an alarm.

CARBON MONOXIDE AND YOUR SAFETY WHAT IS CARBON MONOXIDE (CO)?

You can't taste or smell CO, but it is a very dangerous gas, produced when any fuel burns, High levels of CO can come from appliances that are not operating correctly, or from a venting system or chimney that becomes blocked.

CO CAN BE DEADLY! High levels of CO can make you dizzy or sick (see below).In extreme cases, CO can cause brain damage or death.

Symptoms of CO poisoning include:

- Headache · Shortness of breath
 - Dizziness Nausea
 - Fatigue

冰

IF YOU SUSPECT CO IS PRESENT, ACT IMMEDIATELY!

. If you or a family member shows physical symptoms of CO poisoning, get everyone out of the building and call 911 or your local fire department.

2. If it is safe to do so, open windows to allow entry of fresh air, and turn off any appliances you suspect may be releasing CO.

3. If no one has symptoms, but you suspect that CO is present, call your propane retailer or a qualified service technician to check CO levels and your propane equipment.

TO HELP REDUCE THE RISK OF CO POISONING:

- · Have a qualified service technician check your propane appliances and related venting systems annually, preferably before the heating season begins.
- Install UL-listed CO detectors on every level of your home.
- Never use a gas oven or range top burners to provide space heating.
- · Never use portable heaters indoors unless they are designed and approved for indoor use.
- · Never use barbecue grill (propane or charcoal) indoors for cooking or heating
- · Regularly check your appliance exhaust vents for blockage

SIGNS OF IMPROPER APPLIANCE OPERATION THAT CAN GENERATE HIGH CO LEVELS

- · Sooting, especially on appliances and vents
- · Unfamiliar or burning odor
- · Increased moisture inside of windows

LIGHTING PILOT LIGHTS

IF A PILOT LIGHT REPEATEDLY GOES OUT



or is very difficult to light, there may be a

safety problem. DO NOT try to fix the problem yourself. It is strongly recommended that only a QUALIFIED SERVICE TECHNICIAN light any pilot light that has gone out

YOU ARE TAKING THE RISK of starting a fire or an explosion if you light a pilot light yourself. Carefully follow all the manufacturer's instructions and warnings concerning the appliances before attempting to light the pilot.

APPLIANCE MAINTENANCE



LEAVE IT TO THE EXPERTS. Only a qualified service technician has the training to install, inspect, service, maintain and repair your appliances. Have your appliances and propane systems inspected just before the start of each heating season.

HELP YOUR APPLIANCES "BREATHE." Check the vents of your appliances to be sure that flue gases can flow easily to the outdoors; clear away any insect or bird nests or other debris, Also clear the area around your appliances so plenty of air can reach the burner for proper combustion.


DO NOT TRY TO MODIFIED OR REPAIR valves, regulators, connectors, controls, or other appliance and cylinder tank parts. Doing so creates the risk of a gas leak that can result in property damage, serious injury, or death.

HAVE OLDER APPLIANCE CONNECTORS **INSPECTED.** Certain older appliance connectors may crack or break, causing a gas leak. If you have an appliance that is more than 20 years old, have a qualified service technician inspect the connector. Do not do this yourself, as a movement of the appliance might damage the connector and cause a leak.



FLAMMABLE VAPORS ARE A SAFETY HAZARD. The pilot light on your propane appliance can ignite vapors from gasoline, paint thinners, and other flammable liquids. Be sure to store and use flammable liquids outdoors or in an area of the building containing no propane appliances.

DON'T RISK IT! If you cannot operate any part of your propane system, or if you



RUNNING OUT OF GAS



DON'T RUN OUT OF GAS. SERIOUS SAFETY HAZARDS, INCLUDING FIRE OR **EXPLOSION, CAN RESULT.**

· If an appliance valve or gas line is left open, a leak could occur when the system is recharged with propane.

· If your propane tank runs out of gas, any pilot lights on your appliances will go out. This can be extremely dangerous.

• A LEAK CHECK IS REQUIRED. In many states a propane retailer or a qualified service technician must perform a leak check of your propane system before turning on the gas.