

SERIAL #: SF. UA-085133



ASSEMBLED IN GRIFFIN 23-3199

Model #: RE160i (REU-VE2125FFD-US)

CSA/ANSI Z21.10.3 • CSA 4.3-2019



This water heater requires a special venting system. Refer to the installation instructions for parts list and method of installation. This equipment complies with the requirements of ASHRAE Standard 90.1.

Type of Gas:		Propane Gas
Input Rating	Maximum:	160,000 BTU/H
	Minimum:	10,400 BTU/H
Maximum Inlet Gas Pressure:		13.0"W.C. / (3.24kPa)
Minimum Inlet Gas Pressure:		8.0"W.C. / (1.99kPa)
Min. Inlet Gas Pressure For Adjustments:		11.0"W.C. / (2.74kPa)
Manifold Pressure-High Fire:		4.5"W.C. / (1.12kPa)
Manifold Pressure-Low Fire:		1.1"W.C. / (0.27kPa)
Maximum Water Pressure:		150psi
Nox Emissions:		<77ppm

Suitable for combination water (potable) heating and space heating and not suitable for space heating applications only.

Direct-Vent Automatic Instantaneous Water Heater

DIRECT VENT AUTOMATIC INSTANTANEOUS WATER HEATER FOR INSTALLATION IN A MANUFACTURED HOME (MOBILE HOME)

Minimum clearances from combustibles and non-combustibles:

Back: 0

Front: 0

Top: 2" (51mm)

Sides: 2" (51mm)

Ground: 12" (305mm)

Vent: 0

For Closet Installations, 6" from front