



www.parkergas.com

4163 LITTLE KELLY RD
ROCKY POINT, NC 28457

INVOICE	
Customer #:	3023566
Payment Terms:	Credit Card
Invoice #:	4816127
Invoice Date	2025-01-08
Total Due	\$0.00

Make Check Payable to: Parker Gas Co. Inc.

Amount Enclosed: \$

Remit To:

Parker Gas Co. Inc.

P.O. Box 2590

Clinton, NC 28329-2590

000302356600048161270000000000000000000000004

Customer Name		Delivery/Service Address	Cust #	Invoice #	Inv Date
		8130 US HWY 117 - WILLARD, NC 28478	3023566	4816127	2025-01-08
Quantity	Item Number	Description	Unit Price	TOTAL	
20.00	1/2IN COATED COPPER	COPPER-1/2" COATED REFRIGERATION	\$4.1500	\$83.00	
7.00	1/2IN FLARE NUT	FLARE NUT-1/2"	\$3.7300	\$26.11	
1.00	TRUCK SUPPLIES	TRUCK SUPPLIES	\$7.9500	\$7.95	
5.00	3/4IN CARLON CONDUIT	CARLON CONDUIT-3/4"	\$2.7900	\$13.95	
1.00	POL X POL X 20IN PIGTAIL	PIGTAIL-POL X POL X 20"	\$0.0000	\$0.00	
1.00	1/2IN FPT CUTOFF VALVE	1/2" FEMALE PIPE THREAD CUTOFF VALVE	\$18.0900	\$18.09	
2.00	PRESTO TAP	PRESTO TAP- 1/4"FL X 1/8" MP	\$5.0000	\$10.00	
1.00	1/2IN FLARE X 1/2IN MALE PIPE	ADAPTER-1/2" FL X 1/2" MALE PIPE THREAD	\$4.8900	\$4.89	
1.00	LV3403TR9	REGULATOR-REGO COMPACT FIRST STAGE POL X 1/2	\$0.0000	\$0.00	
1.00	LV4403B66	REGULATOR-REGO SECOND STAGE 3/4 X 3/4	\$64.2400	\$64.24	
1.00	REG BRACKET-STANDARD	REGULATOR BRACKET- REGO STANDARD SIZE SECOND STAGE	\$9.6200	\$9.62	
1.00	3/4IN X 36IN YELLOW FLEX	FLEX CONNECTOR-3/4"x 36" YELLOW	\$26.7600	\$26.76	
1.00	3/4IN FPT CUTOFF VALVE	CUTOFF VALVE-3/4 FPT X 3/4 FPT	\$24.0500	\$24.05	
1.00	RINNAI PLUMB KIT	PLUMBING KIT-RINNAI WATER HEATER	\$71.0000	\$71.00	
1.00	RE160ELP	RINNAI WATER HEATER-RE160E NON-CONDENSING Serial Number: SH.UA-111692	\$858.0000	\$858.00	
1.00	PCD09SHS	RINNAI PIPE COVER FOR RE SERIES	\$175.0000	\$175.00	
1.00	3/4IN GALV TEE	GALVANIZED TEE-3/4"	\$6.3000	\$6.30	
1.00	3/4IN GALV UNION	GALVANIZED UNION-3/4" SCH 40	\$13.4100	\$13.41	
1.00	3/4IN GALV CAP	GALVANIZED CAP-3/4 SCH 40	\$7.0600	\$7.06	
1.00	3/4 GALV ST ELL	GALVANIZED STREET ELBOW-3/4	\$5.1000	\$5.10	
2.00	3/4IN GALV ELBOW	GALVANIZED ELBOW-3/4" 90 DEG SCH 40	\$5.6600	\$11.32	
2.00	3/4IN X 4IN GALV NIPPLE	GALVANIZED NIPPLE-3/4" X 4"	\$5.6800	\$11.36	
6.00	3/4IN X CLOSE GALV NIPPLE	GALVANIZED NIPPLE-3/4 X CL SCH 40	\$6.0600	\$36.36	
1.00	3/4IN X 1/2IN GALV REDUCING	GALVANIZED REDUCING COUPLING-3/4" X 1/2"	\$4.7600	\$4.76	
1.00	1/2IN X CLOSE GALV NIPPLE	GALVANIZED NIPPLE-1/2" X CL SCH 40	\$3.6300	\$3.63	
3.00	Labor-1	Labor-1 Person	\$105.0000	\$315.00	
0.50	Labor-1-Overtime	Labor 1 Person Overtime	\$125.0000	\$62.50	
1.00	LP120AGV	LP120AGV	\$0.0000	\$0.00	
3.00	CONCRETE BLOCK	CONCRETE BLOCK FOR TANK SET	\$0.0000	\$0.00	
1.00	1/2IN FLARE CUTOFF VALVE	CUTOFF VALVE-1/2" FLARE	\$24.7100	\$24.71	
10.00	1/2IN COATED COPPER	COPPER-1/2" COATED REFRIGERATION	\$4.1500	\$41.50	
1.00	1/2IN FLARE TEE	1/2" FLARE TEE	\$5.0300	\$5.03	



www.parkergas.com

Remit To:
Parker Gas Co. Inc.
P.O. Box 2590
Clinton, NC 28329-2590

Parker Gas Co. Inc.
P.O. Box 2590
Clinton, NC 28329-2590
www.parkergas.com

IF YOU SMELL GAS



1. NO FLAMES OR SPARKS! Immediately put out all smoking materials and other open flames. Do not operate lights, appliances, telephones, or cell phones. Flames or sparks from these sources can trigger an explosion or a fire.



2. LEAVE THE AREA IMMEDIATELY! Get everyone out of the building or area where you suspect gas is leaking.



3. SHUT OFF THE GAS. Turn off the main gas supply valve on your propane tank if it is safe to do so. To close the valve, turn it to the right (clockwise).



4. REPORT THE LEAK. From a neighbor's home or other nearby building away from the gas leak, call your propane retailer right away. If you can't reach your propane retailer, call 911 or your local fire department.



5. DO NOT RETURN TO THE BUILDING OR AREA until your propane retailer determines that it is safe to do so.



6. GET YOUR SYSTEM CHECKED. Before you attempt to use any of your propane appliances, your propane retailer or a qualified service technician must check your entire system to ensure that it is leak-free.

CAN YOU SMELL IT?



Propane smells like rotten eggs, a skunk's spray, or a dead animal. Some people may have difficulty smelling propane due to their age (older people may have a less sensitive sense of smell); a medical condition; or the effects of medication, alcohol, tobacco, or drugs. Consider purchasing a propane gas detector as an additional measure of security.

ODOR FADE is an unintended reduction in the concentration of the odor of propane, making it more difficult to smell. Although rare, several situations can cause odor fade:

- The presence of air, water, or rust in a propane tank or cylinder
- The passage of leaking propane through the soil



Since there is a possibility of odor fade or problems with your sense of smell, you should respond immediately to even a faint odor of gas.

PROPANE GAS DETECTORS

Propane Gas Detectors sound an alarm if they sense propane in the air. They can provide an additional measure of security in homes with little-used areas or with occupants who have difficulty smelling propane.

GUIDELINES regarding propane gas detectors:



- Buy only units that are listed by Underwriters Laboratories (UL).



- Follow the manufacturer's instructions regarding installation and maintenance.
- Never ignore the smell of propane, even if no detector is sounding an alarm.

CARBON MONOXIDE AND YOUR SAFETY WHAT IS CARBON MONOXIDE (CO)?

You can't taste or smell CO, but it is a very dangerous gas, produced when any fuel burns. High levels of CO can come from appliances that are not operating correctly, or from a venting system or chimney that becomes blocked.

CO CAN BE DEADLY! High levels of CO can make you dizzy or sick (see below). In extreme cases, CO can cause brain damage or death.

Symptoms of CO poisoning include:

- Headache
- Shortness of breath
- Dizziness
- Nausea
- Fatigue

IF YOU SUSPECT CO IS PRESENT, ACT IMMEDIATELY!



1. If you or a family member shows physical symptoms of CO poisoning, get everyone out of the building and call 911 or your local fire department.



2. If it is safe to do so, open windows to allow entry of fresh air, and turn off any appliances you suspect may be releasing CO.



3. If no one has symptoms, but you suspect that CO is present, call your propane retailer or a qualified service technician to check CO levels and your propane equipment.

TO HELP REDUCE THE RISK OF CO POISONING:

- Have a qualified service technician check your propane appliances and related venting systems annually, preferably before the heating season begins.
- Install UL-listed CO detectors on every level of your home.
- Never use a gas oven or range top burners to provide space heating.
- Never use portable heaters indoors unless they are designed and approved for indoor use.
- Never use barbecue grill (propane or charcoal) indoors for cooking or heating.
- Regularly check your appliance exhaust vents for blockage

SIGNS OF IMPROPER APPLIANCE OPERATION THAT CAN GENERATE HIGH CO LEVELS

- Sooting, especially on appliances and vents
- Unfamiliar or burning odor
- Increased moisture inside of windows

LIGHTING PILOT LIGHTS

IF A PILOT LIGHT REPEATEDLY GOES OUT



or is very difficult to light, there may be a

safety problem. **DO NOT** try to fix the problem yourself. It is strongly recommended that only a **QUALIFIED SERVICE TECHNICIAN** light any pilot light that has gone out

YOU ARE TAKING THE RISK of starting a fire or an explosion if you light a pilot light yourself. Carefully follow all the manufacturer's instructions and warnings concerning the appliances before attempting to light the pilot.

APPLIANCE MAINTENANCE



LEAVE IT TO THE EXPERTS. Only a qualified service technician has the training to install, inspect, service, maintain and repair your appliances. Have your appliances and propane systems inspected just before the start of each heating season.

HELP YOUR APPLIANCES "BREATHE."

Check the vents of your appliances to be sure that flue gases can flow easily to the outdoors; clear away any insect or bird nests or other debris. Also clear the area around your appliances so plenty of air can reach the burner for proper combustion.

DO NOT TRY TO MODIFIED OR REPAIR valves, regulators, connectors, controls, or other appliance and cylinder tank parts. Doing so creates the risk of a gas leak that can result in property damage, serious injury, or death.

HAVE OLDER APPLIANCE CONNECTORS INSPECTED. Certain older appliance connectors may crack or break, causing a gas leak. If you have an appliance that is more than 20 years old, have a qualified service technician inspect the connector. Do not do this yourself, as a movement of the appliance might damage the connector and cause a leak.



FLAMMABLE VAPORS ARE A SAFETY HAZARD. The pilot light on your propane appliance can ignite vapors from gasoline, paint thinners, and other flammable liquids. Be sure to store and use flammable liquids outdoors or in an area of the building containing no propane appliances.



DON'T RISK IT! If you cannot operate any part of your propane system, or if you think an appliance or other device is not working right, call your propane retailer or a qualified service technician for assistance.

RUNNING OUT OF GAS



DON'T RUN OUT OF GAS. SERIOUS SAFETY HAZARDS, INCLUDING FIRE OR EXPLOSION, CAN RESULT.

- If an appliance valve or gas line is left open, a leak could occur when the system is recharged with propane.

- If your propane tank runs out of gas, any pilot lights on your appliances will go out. This can be extremely dangerous.

- **A LEAK CHECK IS REQUIRED.** In many states a propane retailer or a qualified service technician must perform a leak check of your propane system before turning on the gas.