TRANE U.S. INC.
TYLER, TX 75707

NRTL

MODEL NO. SVCC4012A1000AA
SERIAL NO. 2514527 1FA
DATE OF MFG. 04/2025
ELECTRICAL RATING 208/230/60/1
MIN/MAX OPER. VOLT 187 / 253
MAX HACR CKT BRK 40
MAX CKT BRK (CANADIAN INST) 40
CONTROL CKT VOLT 24 VAC
MIN CKT AMP 25
MAX FUSE SIZE 40
MAXIMUM ALLOWABLE PS/MPR: 600.4.1 HIGH 450.2.1 LOW
BR. CKT. SEL. CUR. 18.1
SCCR 5kA rms

COMPR.	QTY	PH	HZ	RLA	LRA
A	1	1	60	14.7	180

INTERNALLY PROTECTED COMPRESSOR

FAN	QTY	PH	HZ	FLA	HP
COND	1	1	60	1.0	1/4
EVAP	1	1	60	6	1/3
EXHAUST	1	1	60	0.5A	1/20

FORCED AIR FURNACE WITH COOLING UNIT, FOR OUTDOOR INSTALLATION ONLY.
-FOURNAISE A AIR PULSE AVEC UNITE DE REFROIDISSEMENT, POUR EXTERIEUR INSTALLATION SEULEMENT.

INSTALL AND MAINTAIN THIS UNIT AS DESCRIBED IN THE MANUALS PROVIDED.
-INSTALLER ET MAINTENIR CET APPAREIL COMME DECRIT DANS LES MANUELS A CONDITION DE

CONFORMS TO ANSI Z21.47 / CSA 2.3-2021
CERTIFIED TO: CSA STD 2.8-2021
CENTRAL FURNACE
FOUR CENTRAL

CLASS/CLASSEMENT

QTY REFRIG CKTS

FACTORY CHARGED: 1

LBS OZ KGS

FORCED AIR FURNACE WITH COOLING UNIT, FOR OUTDOOR INSTALLATION ONLY.
-FOURNAISE A AIR PULSE AVEC UNITE DE REFROIDISSEMENT, POUR EXTERIEUR INSTALLATION SEULEMENT

FACTORY EQUIPPED WITH ORIFICE FOR NATURAL GAS. MINIMUM ARBEN: TEMP 40F. USING EQUIPP DIAMETER POUR LE GAZ NATUREL. TEMP AMBIANTE MINIMALE 40F

PROPANE CONVERSION - USE MANUFACTURER'S KIT AND FOLLOW DIRECTIONS
CONVERSION AU PROPANE - UTILISEZ LA TROUSSE DU FABRICANT ET SUIVEZ LES INSTRUCTIONS

SYSTEM OF DETECTION DE FUITES INSTALLE. L'APPAREIL DOIT ETRE ALIMENTE, SAUF POUR L'ENTRETIEN

Manufactured under one or more of the following U.S. Patents
7,144,219 7,014,425 7,598,473 D629,107 7,391,309

ASSEMBLED IN MEXICO D932414P01

AHRI CERTIFIED

c UL us LISTED
FURNACE

IMPROPER INS

DISCONNECT ALL ELECTRIC POWER INCLUDING
PROCEDURES BEFORE SERVICING.

QUALIFIED INSTALLER, SERVICE AGENCY OR THE
SERVICE. THE FURNACE MUST BE INSTALLED IN A
AND LOCAL CODES. IN THE ABSENCE OF LOCAL CO
OR CAN/CSA-B149.

REFER TO THE OWNER'S MANUAL PROVIDED WITH THIS FU
MAINTENANCE INSTRUCTIONS.

WARNING!

THIS PRODUCT CAN EXPOSE YOU TO CHEMICALS INCLU
CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS O
INFORMATION GO TO WWW.P65WARNINGS.CA.GOV

HAZARDS THAT COULD BE PRESENT AS A RESULT FROM
SERVICE OR WORK CHARGE ARE:

HAZARDOUS VOLTAGE! ROTATING FAN

HAZARDOUS GASES!

UNDESIRABLE RESULT IN CARBON MONOXIDE POISONING, E

FLAMMABLE VAPORS!

THE USE AND STORAGE OF GASOLINE OR OTHER FLAMMABLE
THE VICINITY OF THIS FURNACE CAN RESULT IN EXPLOSION OR
FAILURE TO DO THE ABOVE COULD RESULT IN DEATH, SERIOUS

AVERTISSE

INSTALLATION OU ENTRETIEN

AVERTISSEMENT

TENSION DANGEREUSE!

RAILS DE VENTILATION!

GAZ DANGEREUX!

VAPEURS INFLAMMABLES!

ADVERTENCIA

CAUTION

ATTENTION