





SERIAL # TB UA-014773 

ASSEMBLED IN GRIFFIN 23-3173

Model # RE1801 (REU-VE2432FFD-US)

CSA/ANSI Z21.10.3 • CSA 4.3-2019

This water heater requires a special venting system. Refer to the installation instructions for parts list and method of installation. This equipment complies with the requirements of ASHRAE Standard 90.1.

Type of Gas		Propane Gas
Inlet Rating	Maximum	180,000 BTU/H
	Minimum	10,400 BTU/H
Maximum Inlet Gas Pressure		13.0" W.C. / (3.24kPa)
Minimum Inlet Gas Pressure		8.0" W.C. / (1.99kPa)
Min. Inlet Gas Pressure For Adjustments		11.0" W.C. / (2.74kPa)
Manifold Pressure-High Fire		3.5" W.C. / (0.87kPa)
Manifold Pressure-Low Fire		1.1" W.C. / (0.27kPa)
Maximum Water Pressure		150psi
Nox Emissions		<7ppm

Suitable for combination water (potable) heating and space heating and not suitable for space heating applications only.

Direct-Vent Automatic Instantaneous Water Heater
DIRECT VENT AUTOMATIC INSTANTANEOUS WATER HEATER
FOR INSTALLATION IN A MANUFACTURED HOME (MOBILE HOME)

Maintain clearances from combustibles and non-combustibles:

Back: 0	Front: 0	Top: 2" (51mm)
Sides: 2" (51mm)	Ground: 12" (305mm)	Vent: 0
For Closet Installations, 6" from front		

FOR INDOOR INSTALLATION ONLY
 120 VOLT 60 HZ less than 10 AMPS
 For field-wired connections use No. 14 AWG wires rated for at least 140°F (60°C)

WARNING!

DO NOT USE TOXIC CHEMICALS, SUCH AS AIR USED FOR BOILER TREATMENT, IN HEATING SYSTEMS USED FOR SPACE HEAT.

DO NOT use oil or gas stoves, space heaters, or other combustion appliances in the same room as a water heater.

Rinnai
Nagaya